

Argo

Track Light Series





FEATURES

Mechanical

Body: Aluminium
 Finish: Electrostatic powder painted
 Installation: 3-circuit track mounted
 Diffuser: Transparent safety glass
 Optics: Aluminium reflector

Electrical

Driver: LED driver inside the body.
 Light source: COB LED
 Frequency: 220-240V 50/60 Hz
 Lifetime: 50.000 hours
 Pfc: 0.90
 Operating Temperature: -20 / +50

Options

RAL selection
 CRI>90
 CRI>97
 DALI
 Casambi
 Bluetooth control
 Watt - lumen - efficiency options


Optical

Beam angle: 15-30 degree options
 UGR: <21
 CRI>80
 McAdams Step<3


Specifications




Photometric Data



CCT Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Dimensions (QxH) mm.	Cut-out (mm.)	Weight (kg.)
ITL-105-010-827	10W	900	2700K	60x207	N/A	0,5 kg.
ITL-105-010-830	10W	1010	3000K	60x207	N/A	0,5 kg.
ITL-105-010-840	10W	1100	4000K	60x207	N/A	0,5 kg.
ITL-105-010-865	10W	1180	6500K	60x207	N/A	0,5 kg.
ITL-105-010-800	GU10	-	-	60x207	N/A	0,5 kg.



FEATURES

Mechanical

Body: Aluminium
 Finish: Electrostatic powder painted
 Installation: 3-circuit track mounted
 Diffuser: Transparent safety glass
 Optics: Aluminium reflector

Electrical

Driver: LED driver inside the body.
 Light source: COB LED
 Frequency: 220-240V 50/60 Hz
 Lifetime: 50.000 hours
 Pf>0.90
 Operating Temperature: -20 / +50

Options

RAL selection
 CRI>90
 CRI>97
 DALI
 Casambi
 Bluetooth control
 Watt - lumen - efficiency options


Optical

Beam angle: 15-30-45 degree options
 UGR: <21
 CRI>90
 McAdams Step<3

Specifications




Photometric Data



CCT Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Dimensions (QxH) mm.	Cut-out (mm.)	Weight (kg.)
ITL-106-020-827	20W	1900	2700K	95x195	N/A	0,75 kg.
ITL-106-020-830	20W	2040	3000K	95x195	N/A	0,75 kg.
ITL-106-020-840	20W	2150	4000K	95x195	N/A	0,75 kg.
ITL-106-020-865	20W	2210	6500K	95x195	N/A	0,75 kg.
ITL-106-030-827	30W	3150	2700K	95x195	N/A	0,75 kg.
ITL-106-030-830	30W	3210	3000K	95x195	N/A	0,75 kg.
ITL-106-030-840	30W	3290	4000K	95x195	N/A	0,75 kg.
ITL-106-030-865	30W	3350	6500K	95x195	N/A	0,75 kg.



FEATURES

Mechanical

Body: Aluminium
 Finish: Electrostatic powder painted
 Installation: 3-circuit track mounted
 Diffuser: Transparent safety glass
 Optics: Aluminium reflector

Electrical

Driver: LED driver inside the body.
 Light source: COB LED
 Frequency: 220-240V 50/60 Hz
 Lifetime: 50.000 hours
 Pf>0.90
 Operating Temperature: -20 / +50

Options

RAL selection
 CRI>90
 CRI>97
 DALI
 Casambi
 Bluetooth control
 Watt - lumen - efficiency options


Optical

Beam angle: 15-30-45 degree options
 UGR: <21
 CRI>90
 McAdams Step<3

Specifications




Photometric Data



CCT Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Dimensions (QxH) mm.	Cut-out (mm.)	Weight (kg.)
ITL-106-036-827	36W	3750	2700K	95x195	N/A	0,75 kg.
ITL-106-036-830	36W	3850	3000K	95x195	N/A	0,75 kg.
ITL-106-036-840	36W	3950	4000K	95x195	N/A	0,75 kg.
ITL-106-036-865	36W	4050	6500K	95x195	N/A	0,75 kg.