



FEATURES

Mechanical

Body: Aluminium
Finish: Electrostatic powder painted
Installation: Wall Recessed

Options

RAL selection
CRI>90
CRI>97


Electrical

Driver: LED driver inside body
Light source: MiD Power LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pfc>0.90
Operating Temperature: -20 / +50

Optical

UGR: <21
CRI>80

Specifications




Photometric Data

CCT Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Dimensions (WxLxH) mm.	Cut-out (mm.)	Weight (kg.)
EUS-905-005-830	5W	569	3000K	100x100x72	96mm	0,4 kg.
EUS-905-005-840	5W	600	4000K	100x100x72	96mm	0,4 kg.
EUS-905-005-865	5W	675	6500K	100x100x72	96mm	0,4 kg.



FEATURES

Mechanical

Body: Aluminium
Finish: Electrostatic powder painted
Installation: Wall Recessed

Options

RAL selection
CRI>90
CRI>97


Electrical

Driver: LED driver inside body
Light source: MiD Power LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pfc>0.90
Operating Temperature: -20 / +50

Optical

UGR: <21
CRI>80

Specifications




Photometric Data

CCT Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Dimensions (WxLxH) mm.	Cut-out (mm.)	Weight (kg.)
EUS-907-006-830	6W	540	3000K	195x195x85	171	0,5 kg.
EUS-907-006-840	6W	570	4000K	195x195x85	171	0,5 kg.
EUS-907-006-865	6W	600	6500K	195x195x85	171	0,5 kg.