



FEATURES

Mechanical

Body: Aluminium
Finish: Electrostatic powder painted
Installation: Surface mounted
Optics: PMMA plexiglass

Options

DALI
Length options

Electrical

Driver: LED driver inside the body
Light source: Power LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pfc>0.90
Operating Temperature: -20 / +50

Optical

Beam angle: Symmetrical
CRI>80
McAdams Step<3

Specifications




Light Beam

Kelvin Values



Technical Drawing



Art. No.	Watt	Lumen	CCT	Weight (kg.)	Dimensions (WxLxH) mm.
EUS-921-030-830	30W	3100	3000K	8,2 Kg.	80(W) x 4000(L) x 150(H)
EUS-921-030-840	30W	3175	4000K	8,2 Kg.	80(W) x 4000(L) x 150(H)
EUS-921-030-850	30W	3310	5000K	8,2 Kg.	80(W) x 4000(L) x 150(H)
EUS-921-040-830	40W	4230	3000K	8,9 kg.	80(W) x 5000(L) x 150(H)
EUS-921-040-840	40W	4400	4000K	8,9 kg.	80(W) x 5000(L) x 150(H)
EUS-921-040-850	40W	4550	5000K	8,9 kg.	80(W) x 5000(L) x 150(H)
EUS-921-060-830	60W	6200	3000K	9,9 kg.	80(W) x 6000(L) x 150(H)
EUS-921-060-840	60W	6450	4000K	9,9 kg.	80(W) x 6000(L) x 150(H)
EUS-921-060-850	60W	6600	5000K	9,9 kg.	80(W) x 6000(L) x 150(H)