




Specifications



Light Beam

Kelvin Values



FEATURES

Mechanical

Body: Aluminium
 Finish: Electrostatic powder painted
 Installation: Surface mounted
 Optics: PMMA plexiglass

Options

DALI
 Length options


Electrical

Driver: LED driver inside the body
 Light source: Power LED
 Frequency: 220-240V 50/60 Hz
 Lifetime: 50.000 hours
 Pfc0.90
 Operating Temperature: -20 / +50

Optical

Beam angle: Symmetrical
 CRI>80
 McAdams Step<3

Technical Drawing



Art. No.	Watt	Lumen	CCT	Weight (kg.)	Dimensions (WxLxH) mm.
EUS-920-030-830	30W	3100	3000K	7,2 Kg.	60(W) x 3000(L) x 60(H)
EUS-920-030-840	30W	3175	4000K	7,2 Kg.	60(W) x 3000(L) x 60(H)
EUS-920-030-850	30W	3310	5000K	7,2 Kg.	60(W) x 3000(L) x 60(H)
EUS-920-040-830	40W	4230	3000K	8,2 Kg.	60(W) x 4000(L) x 60(H)
EUS-920-040-840	40W	4400	4000K	8,2 Kg.	60(W) x 4000(L) x 60(H)
EUS-920-040-850	40W	4550	5000K	8,2 Kg.	60(W) x 4000(L) x 60(H)
EUS-920-060-830	60W	6200	3000K	8,9 kg.	60(W) x 5000(L) x 60(H)
EUS-920-060-840	60W	6450	4000K	8,9 kg.	60(W) x 5000(L) x 60(H)
EUS-920-060-850	60W	6600	5000K	8,9 kg.	60(W) x 5000(L) x 60(H)



Specifications

CRI
≥80

POWER
LED

IP65

IK08

CE

UK
CA

Light Beam

Kelvin Values



FEATURES

Mechanical

Body: Aluminium
Finish: Electrostatic powder painted
Installation: Surface mounted
Optics: PMMA plexiglass

Options

DALI
Length options


Electrical

Driver: LED driver inside the body
Light source: Power LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pfc0.90
Operating Temperature: -20 / +50

Optical

Beam angle: Symmetrical
CRI>80
McAdams Step<3

Technical Drawing



Art. No.	Watt	Lumen	CCT	Weight (kg.)	Dimensions (WxLxH) mm.
EUS-920-080-830	80W	8180	3000K	9,9 kg.	60(W) x 6000(L) x 60(H)
EUS-920-080-840	80W	8300	4000K	9,9 kg.	60(W) x 6000(L) x 60(H)
EUS-920-080-850	80W	8550	5000K	9,9 kg.	60(W) x 6000(L) x 60(H)
EUS-920-120-830	120W	12000	3000K	9,9 kg.	60(W) x 6000(L) x 60(H)
EUS-920-120-840	120W	13250	4000K	9,9 kg.	60(W) x 6000(L) x 60(H)
EUS-920-120-850	120W	14000	5000K	9,9 kg.	60(W) x 6000(L) x 60(H)