MAGNA D I

Categories: Interior, Magnet Lighting

Mechanical

Body : Aluminium
Finish: Electrostatic powder paint
Optics: Dark optic lenses
Installation: 48V magnetic track mounted

Electrical

Light source: MID POWER LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pf>0.90
Operating Temperature: -20 / +50

Optical

Light effect: Fixed
Beam angle: 24 degrees
UGR: <19
CRI>80
McAdams Step<3

Options

RAL selection
CRI>90
DALI
Casambi - Bluetooth control

CE UK CA CRI ≥80 MID POWER LED IP 20

Photometric Data

24°



Technical Drawing



Art. No.	Power	Lumen	Colour Temperature	Dimensions (WxLxH) mm.	Cut-out (mm.)	Weight (kg.)
IMS-306-006	6W	650*	2700K-6500K	22x112x44	N/A	0,30 kg.
IMS-306-012	12W	1360*	2700K-6500K	22x219x44	N/A	0,60 kg.
IMS-306-018	18W	2000*	2700K-6500K	22x326x44	N/A	1,00 kg.
IMS-306-024	24W	2530*	2700K-6500K	22x438x44	N/A	1,20 kg.

Lumen values can vary according to CCT - CRI and beam angle options