MAGNA S

Categories: Interior, Magnet Lighting

Mechanical

Body : Aluminium
Finish: Electrostatic powder paint
Optics: Aluminium reflector
Installation: 48V magnetic track mounted

Electrical

Light source: COB LED
Frequency: 220-240V 50/60 Hz
Lifetime: 50.000 hours
Pf>0.90
Operating Temperature: -20 / +50

Optical

Light effect: Directional, 180° vertical, 350° horizontal
Beam angle: 24 degrees
UGR: <21
CRI>80
McAdams Step<3

Options

RAL selection
CRI>90
DALI
Casambi - Bluetooth control

CE UK CA CRI ≥80 COB LED IP 20 180° 350°

Photometric Data

24°



Technical Drawing



Art. No.	Power	Lumen	Colour Temperature	Dimensions (QxH1xH2) mm.	Cut-out (mm.)	Weight (kg.)
IMS-303-007	7W	740*	2700K-6500K	35x80x120	N/A	0,30 kg.
IMS-303-012	12W	1320*	2700K-6500K	55x120x160	N/A	0,50 kg.
IMS-303-024	24W	2600*	2700K-6500K	60x130x170	N/A	0,90 kg.

Lumen values can vary according to CCT - CRI and beam angle options