

### Mechanical

Body : Extruded aluminium  
 Finish: Electrostatic powder paint  
 Optics: Opal diffuser  
 Installation: Surface mounted

### Electrical

Driver: LED driver inside the body  
 Light source: SMD LED  
 Frequency: 220-240V 50/60 Hz  
 Lifetime: 50.000 hours  
 Pf>0.90  
 Operating Temperature: -20 / +50


### Optical

Light effect: Direct  
 Beam angle: 120 degrees  
 UGR: <21  
 CRI>80  
 McAdams Step<3

### Options

RAL selection  
 CRI>90  
 DALI-1-10V-Phase dimming  
 Casambi - Bluetooth control  
 Emergency kit - CBS connection  
 IP54 protection

### Photometric Data



### Technical Drawing



| Art. No.    | Power | Lumen | Colour Temperature | Dimensions (WxLxH) mm. | Cut-out (mm.) | Weight (kg.) |
|-------------|-------|-------|--------------------|------------------------|---------------|--------------|
| ITS-920-006 | 6W    | 700*  | 2700K-6500K        | 61x311x35              | N/A           | 0,35 kg.     |
| ITS-920-010 | 10W   | 1200* | 2700K-6500K        | 61x630x35              | N/A           | 0,56 kg.     |